



US009409043B2

(12) **United States Patent**  
**Franken**

(10) **Patent No.:** **US 9,409,043 B2**  
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **GLASS BREAKING TOOL, METHOD FOR  
BREAKING GLASS**

(75) Inventor: **Johannes Baptist Martinus Franken,**  
Zoetermeer (NL)

(73) Assignee: **LIFE SAFETY PRODUCTS B.V.,**  
Zoetermeer (NL)

(\*) Notice: Subject to any disclaimer, the term of this  
patent is extended or adjusted under 35  
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/822,537**

(22) PCT Filed: **Sep. 9, 2011**

(86) PCT No.: **PCT/NL2011/050618**

§ 371 (c)(1),  
(2), (4) Date: **May 22, 2013**

(87) PCT Pub. No.: **WO2012/036548**

PCT Pub. Date: **Mar. 22, 2012**

(65) **Prior Publication Data**

US 2013/0227795 A1 Sep. 5, 2013

(30) **Foreign Application Priority Data**

Sep. 13, 2010 (NL) ..... 2005342

(51) **Int. Cl.**  
**B26B 11/00** (2006.01)  
**A62B 3/00** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **A62B 3/005** (2013.01); **Y10T 29/4998**  
(2015.01); **Y10T 225/371** (2015.04)

(58) **Field of Classification Search**

CPC . A62B 3/005; Y10T 225/371; Y10T 29/4998

USPC ..... 7/158; 81/20

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

947,391	A *	1/1910	Michael	30/367
1,572,046	A *	2/1926	Seiler	30/367
2,787,179	A	4/1957	Warner	
3,172,204	A *	3/1965	Frey	30/367
3,900,058	A *	8/1975	McArdle	81/463
4,682,412	A *	7/1987	Pfeffer	29/750
5,360,211	A *	11/1994	Smith et al.	267/180
5,657,543	A *	8/1997	Collins	30/367
5,791,056	A	8/1998	Messina	
6,079,071	A	6/2000	Sablan et al.	

(Continued)

FOREIGN PATENT DOCUMENTS

CN	200955930	10/2007
DE	4016612	11/1991

(Continued)

OTHER PUBLICATIONS

Office Action from the corresponding Chinese Application No.  
2011800546284 dated Oct. 20, 2014.

*Primary Examiner* — Hadi Shakeri

*Assistant Examiner* — Danny Hong

(74) *Attorney, Agent, or Firm* — Lucas & Mercanti, LLP

(57) **ABSTRACT**

A glass breaking tool for breaking a glass pane comprising a head arranged for contact with the glass pane, a handle movable with respect to the head and a pin crusher arranged in the head and handle wherein the tool is adjustable between a rest position in which the pin crusher is locked inside the head, a releasing position in which the pin crusher is released inside the head and a breaking position in which a tip of the pin crusher is at least partially outside the head.

**20 Claims, 6 Drawing Sheets**

